

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 13 in the underlying PCT Application No. PCT/FR03/00608 and adds new claims 14 to 25. The new claims, inter alia, conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.121(b)(3), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(iii) and 1.125(b)(2), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.

The underlying PCT Application No. PCT/FR03/00608 includes an International Search Report, dated August 22, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: 9/1/04

By: John M. Vereb
John M. Vereb
Reg. No. 48,912

One Broadway
New York, New York 10004
(212) 425-7200

12428/b018
10/506481

METHOD FOR DESIGNING A NUCLEAR FUEL ASSEMBLY HAVING A
DAMPING GUIDE TUBE, A CORRESPONDING SYSTEM, COMPUTER
PROGRAM AND MEDIUM

DT09 Rec'd PCT/PTO 01 SEP 2004

[Method for designing a nuclear fuel assembly having a
damping guide tube, a corresponding system, computer
programme and medium] FIELD OF THE INVENTION

The present invention relates to a method for designing a
5 nuclear fuel assembly which is intended to be positioned
in a nuclear reactor, the assembly comprising a plurality
of guide tubes, and a control cluster which itself
comprises a plurality of control rods and a support for
control rods, the control rods and the guide tubes
10 extending in parallel with a longitudinal direction, each
control rod being received in a guide tube in order to
form pairs comprising guide tubes/control rods, each
guide tube comprising a lower damping portion which
comprises at least a portion of reduced inside diameter,
15 which portion is intended to contain a fluid for damping
the fall of the control rod which is received in the
guide tube, the portion of reduced inside diameter
surrounding the control rod with a radial passage gap
when the control rod enters the guide tube.

20

BACKGROUND INFORMATION

It will be appreciated that nuclear fuel assemblies must
be dependable in order to allow reliable operation of
nuclear reactors. [
25]Thus, design and construction provisions for such
assemblies have been drawn up.

These provisions impose a general framework and minimum
criteria which the assembly constructors must take into
30 consideration.

As far as the guide tubes are concerned, the design provisions require verification that they remain stable under axial compression and that the mechanical integrity thereof is not affected during such compression. These
5 criteria are aimed in particular at taking into consideration the axial compression of the guide tubes which results from contact against the upper bearing plate of the core by springs carried by an upper end piece of the assembly.

10

Although the criteria imposed by the design provisions allow assemblies to be designed with satisfactory reliability, these are merely minimum criteria and it is desirable to develop a method
15 which allows even more reliable assemblies to be designed.

For all that, it is also desirable to reduce the safety margins during design in order to reduce the
20 mass and the cost of the assemblies constructed.

SUMMARY OF THE INVENTION

An objective [An object] of the invention is to overcome this problem by providing a method which
25 allows nuclear fuel assemblies which are more reliable to be designed, [whilst] while limiting the design margins.

To this end, the invention relates to a method for
30 designing a nuclear fuel assembly which is intended to be positioned in a nuclear reactor, the assembly comprising a plurality of guide tubes, and a control cluster which itself comprises a plurality of control rods and a support for control rods, the control rods

and the guide tubes extending in parallel with a longitudinal direction, each control rod being received in a guide tube in order to form pairs comprising guide tubes/control rods, each guide tube comprising a lower damping portion which comprises at least a portion of reduced inside diameter, which portion is intended to contain a fluid for damping the fall of the control rod which is received in the guide tube, the portion of reduced inside diameter surrounding the control rod with a radial passage gap when the control rod is introduced in the guide tube, [characterised in that] wherein the method comprises, for at least one pair comprising a guide tube/control rod, the following steps:

15

a) establishing the falling speed of the control rod upon entry into the lower damping portion when the control cluster falls in the event of a shutdown of the nuclear reactor,

20

b) establishing, based on the falling speed established in step a), the progression of the falling speed of the control rod in the lower damping portion,

25

c) establishing, based on the progression of the speed established in step b), a maximum elevated pressure produced in the liquid contained in the lower damping portion, and

30

d) establishing, based on the maximum elevated pressure established in step c), a maximum circumferential stress produced in the lower damping portion.

According to specific embodiments, the method can
comprise one or more of the following features, taken
in isolation or according to all technically feasible
5 combinations:

- the method further comprises a step for verifying,
using the maximum circumferential stress established
in step d), that a maximum stress admissible by the
10 guide tube has not been exceeded,

- the establishing step b) is carried out using a
higher value for the radial passage gap and the
establishing step c) is [carried out] performed using
15 a lower value for the radial passage gap,

- the higher value is a maximum statistical value for
the passage gap,

20 - the lower value is a minimum statistical value for
the passage gap,

- the support of the control cluster comprising a
helical spring for damping the impact of the support
25 against an upper end piece of the assembly in the
event of the control cluster falling during a
shutdown of the nuclear reactor[, the] The method
further comprises the following steps:

30 e) establishing the progression of the speed of the
control cluster after the impact of the support
against the upper end piece,

f) establishing, based on the progression of the speed established in step e), a maximum longitudinal load for compression of the spring, and

5 g) establishing, based on the maximum longitudinal load for compression, at least a maximum shearing stress in the spring,

- a maximum shearing stress is a shearing stress
10 along the neutral axis of the spring,

- a maximum shearing stress is a shearing stress along the axis of the spring nearest the longitudinal [centre] center axis thereof,

15 - the method further comprises a step for verifying, using a maximum shearing stress established in step g), that a maximum stress admissible by the spring has not been exceeded.

20 The invention further relates to a system for designing a nuclear fuel assembly, characterised in that it comprises [means for carrying out] an arrangement for performing the steps of a method as
25 defined above.

According to a variant, the system comprises a computer and storage [means] arrangement, in which at least a [programme] program comprising instructions
30 for [carrying out] performing steps of the method for designing a nuclear fuel assembly is stored.

The invention further relates to a computer [programme] program comprising instructions for

[carrying out] performing the steps of a method as defined above.

The invention also relates to a medium which can be
5 used in a computer and on which a [programme] program
as defined above is recorded.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood from a reading
10 of the description below which is given purely by way
of example with reference to the appended drawings[,
in which:] _

Figure 1 is a schematic, perspective cut-away view of
15 a nuclear fuel assembly which is designed by a method
according to the invention[,] _

Figure 2 is a schematic, partially sectioned side
view drawn to an enlarged scale of the structure of
20 the spider of the assembly of Figure 1[,] _

Figure 3 is a partial schematic side view of the
assembly of Figure 1, illustrating more particularly
a pair comprising a guide tube/control rod[,] _
25

Figure 4 is a block diagram illustrating the system
for designing the assembly of Figure 1[,] _

Figure 5 is a flow chart illustrating successive steps of
30 the design method carried out by the system of Figure
4[,] _

Figure 6 is a progression curve of the falling speed of a
control rod before it is introduced in the lower portion

of the corresponding guide tube, this progression being calculated by the system of Figure 4[, and]_.

Figure 7 is a progression curve of the falling speed of
5 the same control rod in the lower portion of the corresponding guide tube, this progression being calculated by the system of Figure 4.

DETAILED DESCRIPTION

10 Figure 1 illustrates a nuclear fuel assembly 1 which mainly comprises a square-based lattice 2 for nuclear fuel rods 3 and a control cluster 4.

The assembly 1 comprises grids 5 for maintaining the rods
15 3, which grids 5 are distributed over the height of the rods 3. A lower end piece 6 is arranged under the lower ends of the rods 3 and an upper end piece 7 above the upper ends of the rods 3. The upper end piece 7 is provided with springs 8 for pressing against the upper
20 bearing plate of the reactor core, in which the assembly 1 is intended to be placed.

The control cluster 4 comprises a plurality of control rods 10, for example, 24. Conventionally, the control
25 rods 10 comprise a material which absorbs neutrons.

The rods 3 and 10 extend in parallel with a vertical longitudinal direction L.

30 The rods 10 are carried at the upper ends thereof by a support 11 which is generally referred to as a spider.

As illustrated more particularly in Figure 2, the spider 11 comprises a vertical central upper head 12 and a

series of arms or vanes 13 which extend radially outwards from the lower end of the upper head 12 as far as the radially outer ends 14 thereof.

- 5 Each control rod 10 is connected to an arm 13 at the upper end thereof.

The upper head 12 of the spider 11 has a central blind hole 15 which opens towards the bottom and in which a
10 damping helical spring 16 is received. The spring 16 extends vertically along a [centre] center axis A. A tightening screw 17 extends substantially over the entire height of the hole 15 and is screwed into the wall 18 delimiting the upper portion of the hole 15.

15 The lower portion of the screw 17 extends through the base of a retaining ring 20 which rests on the lower end of the spring 16. The head 21 of the screw 17 rests, at the top, against the base of the retaining ring 20 in
20 order to press the spring 16 against the wall 18 of the upper head 12.

As illustrated in Figure 3 for a control rod 10, each control rod 10 is received in a respective guide tube 24
25 which is arranged in the lattice 2 of fuel rods 3. In this manner, 24 pairs comprising a guide tube/control rod are formed. Since each of these pairs has a similar structure, only one will be described below.

30 The guide tube 24 extends from the lower end piece 6 as far as the upper end piece 7. The guide tube 24 comprises a lower portion 26 of reduced inside diameter and an upper portion 27. The lower portion 26 is connected

to the lower end piece 6 by a collared screw 28,
through which a vertical through-hole 29 extends.

The lower portion 26 of the guide tube 24 surrounds
5 the control rod 10 with a radial passage gap J.

The upper portion 27 is fixed to the upper end piece 7
and opens at the outside of the assembly 1.

10 Lateral apertures 30, only one of which can be seen
in Figure 4, are provided in the upper portion 27 near
the lower portion 26.

When the assembly 1 is placed in a nuclear reactor,
15 the cooling liquid of the reactor fills the interior
of the guide tube 24.

Conventionally, the control cluster 4 can be moved
vertically relative to the remainder of the assembly 1
20 in order to allow adjustment of the reactivity during
normal operation of the reactor, and therefore
variations in power from zero power up to maximum
output depending on the vertical introduction of the
control rods 10 in the lattice 2 of rods 3. The
25 vertical displacement of the control cluster 24 is
conventionally [carried out] performed by way of a
drive rod which is connected to the upper end of the
upper head 12.

30 When the reactor is shut down, the drive rod and the
assembly 4 fall [owing] due to gravity.

At the start of this falling movement, the control
rods 10 are guided only by the upper portions 27 of

the guide tubes 24 and have not yet reached the lower portions 26.

Once the falling action has ended, the lower ends of
5 the control rods 10 are introduced in the lower portions 26. The cooling fluid contained in the portions 26 is then violently forced, on the one hand, upwards thereby and, on the other hand, downwards through the apertures 29 of the collared
10 screws 28.

Each lower portion 26 therefore behaves in the manner of a hydraulic damper braking the falling movement of the corresponding control rod 10, and therefore of
15 the assembly 4.

This braking phase ends at the end of the travel path with the impact of the spider 11 against the upper end piece 7 of the assembly 1.

20

This impact is [carried out by means of] performed by a the retaining ring 20. During this impact, the spring 16 is compressed vertically in order to absorb the shock.

25

According to the invention, the assembly 1 has been designed in order to take into consideration the specific stresses brought about in the assembly by the fall of the control cluster 4 during such a
30 shutdown of the reactor.

In this manner, in order to design the assembly 1, in particular a data-processing system 32 has been used, as illustrated schematically in Figure 4.

This system 32 comprises, for example, a computer or data processing unit 34 comprising one or more processors, storage [means] arrangement 36, input/output [means] arrangement 38, and optionally display [means] arrangement 40.

Instructions which can be [carried out] performed by the computer 34 are stored in the form of one or more [programmes] programs in the storage [means] arrangement 36.

These instructions are, for example, instructions in FORTRAN programming code.

15

These various instructions, when they are [carried out] performed by the computer 34, allow the method illustrated by the flow chart of Figure 5 to be [carried out] performed.

20

In a first step illustrated by the box 42 of this [Figure] figure, the computer 34 calculates, based on data 43, the progression of the falling speed of a control rod 10 in the upper portion 27 of the corresponding guide tube 24 in the event of a shutdown of the reactor.

This calculation can be [carried out] performed assuming, for example, that the control rod 10 is first subjected to constant loads:

- gravitational force: $f_g = Mg$,
- [Archimedes'] Archimedes' thrust: $f_a = -p \cdot gV$,
- pressure difference in the core: f_c , and
- mechanical friction: f_m ,

where M and V are the mass and the volume, respectively, of the assembly 4 and the drive rod thereof.

5

The control rod 10 is also subjected to loads as a function of the speed or position thereof, for example, hydraulic friction which can be obtained from: $f_h = -[c_1] \frac{c_1}{M + pV} v^2$, with v = speed of the
10 assembly 4 and therefore of the rod 10 in question.

Thus, the equation of the movement of the rod in the upper portion 27 of the guide tube 24 is as follows:

15
$$(M + pV) \frac{dv}{dt} = \Sigma f$$

This gives:

$$\frac{dv}{dt} = c_2 - c_1 v^2$$

with c_1 = hydraulic friction in the guide tube and

$$c_2 = \frac{f_g + f_a + f_c + f_m}{M + pV}$$

20 c_1 and c_2 are, for example, experimental data measured during drop tests of the control cluster 4. These data are, with the other data necessary for the calculation, such as the mass and the volume of the assembly 4 and the drive rod thereof, introduced, for
25 example, in the form of a file 43 by way of the input/output [means] arrangement 38.

The computer 34 resolves the equation of the movement of the control rod 10, for example, using the NEWTON
30 method.

Thus, the progression of the speed of the control rod 10 in the upper portion 27 is known as a function of time. The profile established in this manner can be displayed in the form of a curve by the display

5 [means] arrangement 40. This curve is illustrated by Figure 6.

In this manner, at the end of the step illustrated by the box 42, the speed of the control rod 10 is known
10 at the point of entry to the lower damping portion 26 of the guide tube 24.

Based on the results of the step of box 42, the computer 34 calculates the progression of the speed
15 of the control rod 10 during its fall in the lower damping portion 26.

This step is schematically illustrated by [the] box
44.

20

This step can be [carried out] performed using the following equation:

$$-\frac{dv}{dt} = c2 - \left(cl + \frac{SCAxNCA\Delta P}{M + pV v^2} \right) v^2$$

$$\text{with } c2 = \frac{fg + fa}{M + pV} = \frac{M - pV}{M + pV} g$$

25 SCA = cross-section of the rod 10 and
NCA = number of rods 10 in the assembly 4.

Therefore, the hypothesis that f_c and $f_{m_}$ are negligible is applied here.

30

The difference ΔP represents the elevated pressure produced in the cooling liquid contained in the guide

tube 24, [that is to say] for example, the pressure thereof between the lower end of the rod 10 and the pressure present in the upper portion 27 of the guide tube 24.

5

ΔP can be established by the following formula:

$$\Delta P = \frac{1}{2} p Q^2 v^2 (EXPA + CONTRA + FECR \times CISA \times z)$$

$$\text{where } EXPA = \left(\frac{SCA}{SACM} \left(1 - \frac{SACM}{SACTG} \right) \right)^2$$

with SM = cross-section of the lower portion 26,

10 SACM = SM - SCA = cross-section of the annular space between the rod 10 and the lower portion 26,
SACTG = STG - SCA, where STG is the cross-section of the upper portion 27 of the guide tube 24,

15

$$CONTRA = 0.4 \left(1 - \frac{SACM}{SM} \right) \left(\frac{SCA}{SACM} \right)^2$$

FECR = coefficient of loss of load owing to friction in the lower portion 26,

20

$$CISA = \left(\frac{SCA}{SM} \right)^2 \frac{1}{DM}$$

DM = mean diameter of the guide tube 24 in the upper portion 27,

z = height of the rod 10 introduced in the lower portion 26 of the guide tube 24, and

25 Q = fraction of liquid flowing upwards out of the lower portion 26.

The resolution of the equations governing the movement of the rod 10 after entry into the lower

portion 26 is carried out by the computer 34, for example, using the RUNGE-KUTTA method.

Thus, at the end of [the] step 44, the progression of
5 the speed of the control rod 10 in the lower portion
26 of the guide tube 24 is known before the impact of
the spider 11 on the upper end piece 7.

The speed profile established in this manner can be
10 displayed, for example, by the [means] arrangement
40, as illustrated in Figure 7. On the curve in
[Figure] figure 7, the speed profile established
during step 44 is the portion located to the left of
the point 45.

15

The computer 34 then [carries out] performs, in the
step of box 46, the calculation of the maximum
elevated pressure produced ΔP_{MAX} .

20 This calculation can be [carried out] performed, for
example, based on the formula:

$$\Delta P = \frac{1}{2} p Q^2 v^2 (EXPA + CONTRA + FECRxCISAxz).$$

The computer 34 [carries out] performs, in the step
25 [of box] 48, the calculation of a circumferential
stress and maximum normal $\sigma_{\theta MAX}$, to which the lower
portion 26 of the guide tube 24 is subjected [owing]
due to the maximum elevated pressure ΔP_{MAX} .

30 This stress can be calculated based on the formula:

$$\sigma_{\theta MAX} = \frac{1}{2} \Delta P_{MAX} \left(\frac{DPM}{EMP} + 1 \right)$$

where DPM = inside diameter of the lower portion 26
and []EMP = minimum thickness of the wall of the
lower portion 26.

5 The system 32 can then provide, [owing] due to the
input/output [means] arrangement 38, a first result
in the form of a file 49 containing the value $\sigma_{\theta MAX}$
established, and optionally the maximum elevated
pressure ΔP_{MAX} established.

10

Next, the system 32 [carries out] performs the
calculation of the progression of the speed of the
control rod 10 after it comes into contact with the
spider 11 and the upper end piece 7.

15

This calculation step is illustrated by the box 50 in
Figure 5.

This calculation can be [carried out] performed, for
20 example, using the following equation when the ring
20, and therefore the spider 11, is in contact with
the upper end piece 7:

$$(M + pV) \frac{dv}{dt} = (M - pV)g - PRCH - K(z - LAI) - c3v$$

with PRCH = preload of the spring 16 = PRCMP x K,
25 where PRCMP is the precompression of the spring 16
and K the rigidity of the spring 16,
LAI = distance travelled by the control rod in the
lower portion 26 before impact, and
c3 = coefficient of hydraulic damping in order to
30 model the damping in the lower portion 26.

In the event of a rebound, [that is to say] for
example, when the spider 11 is no longer in contact

with the upper end piece 7, the equation for movement of the control rod 10 in question is written as follows:

$$5 \quad (M + PV) \frac{dv}{dt} = (M - pV)g - c3v$$

These two equations are integrated by the computer 34, for example, using the RUNGE-KUTTA method.

Therefore, the step 50 allows the kinematics of the control cluster 4 to be established during the mechanical damping of the shock by the spring 16. The speed profile established in this manner can be displayed, for example, by the [means] arrangement 40. This profile corresponds to the portion located to the right of the point 45 on the curve in Figure 7.

Based on the results of this step, the system 32 [carries out] performs, in the step 52, the calculation of a maximum vertical compression force F_{MAX} , to which the spring 16 is subjected during the mechanical damping.

This calculation can be carried out, for example, based on the following formula:

$$F_{MAX} = \max \{ K(z - LAI) + PRCH \}$$

The system 32 then [carries out] performs, in the step of box 54, the calculation of an approximate maximum shearing stress τ_{MAX} in the spring 16:

$$30 \quad \tau_{MAX} = \frac{8F_{MAX}DFN}{\pi DFR^3}$$

with $DFN = DER - DFR$ and

DER = outside diameter of the spring 16,
DFR = diameter of the wire of the spring 16.

Subsequently, the system 32 can optionally [carry
5 out] perform, based on the maximum stress τ_{MAX} , the
calculation of maximum corrected stresses.

These stresses can be calculated by multiplying τ_{MAX}
by different factors.

10

Thus, it is possible to calculate:

$$\tau_{MAX1} = \tau_{MAX} \times K_c \text{ and}$$

$$\tau_{MAX2} = \tau_{MAX} \times K$$

$$\text{with } K_c = 1 + \frac{0.5}{C},$$

$$C = \frac{DFN}{DFR}, \text{ and}$$

$$K = \frac{4C-1}{4C-4} + \frac{0.615}{C}$$

15 $\tau_{MAX1} = \tau_{MAX} \times K_c, \text{ and}$

$$\tau_{MAX2} = \tau_{MAX} \times K,$$

$$\text{with } K_c = 1 + 0.5/C,$$

$$C = DFN/DFR, \text{ and}$$

20 $K = (4C-1)/(4C-4) + 0.615/C$

The stress τ_{MAX1} corresponds to the shearing stress
along the neutral axis FN (Figure 2) of the spring
16. The stress τ_{MAX2} corresponds to the stress along
25 the axis F2 (Figure 2) of the spring 16 nearest the
vertical [centre] center axis A of the spring 16 (see
Figure 2).

At the end of this step illustrated by the box 56, the system 32 provides the various maximum shearing stresses calculated, for example, in the form of data stored in a file 57, which are transmitted by the
5 input/output [means] arrangement 38.

Based on the data contained in the files 49 and 57, which have also been stored in the storage means 36, the computer 34 will verify that the maximum stresses
10 calculated are indeed acceptable for the materials which respectively constitute the guide tube 24 and the helical spring 16.

This step has been schematically illustrated by the
15 box 58 in Figure 5. During such a step, the system 32 will, for example, verify that the maximum shearing stresses calculated during the steps 54 and 56 are less than maximum values admissible by the material which constitutes the spring 16. This verification is
20 [carried out] performed by a comparison of τ_{MAX} , τ_{MAX1} and τ_{MAX2} with a maximum value admissible by the material of the spring 16.

As far as the maximum circumferential stress $\sigma_{\theta MAX}$ is
25 concerned, the verification can be carried out based on a formula of the type:

$$f(\sigma_{\theta MAX}) < \sigma_{admissible}$$

30 where $\sigma_{admissible}$ refers to the material which constitutes the lower portions 26 of the guide tubes 24.

The function f can be a function which takes into consideration other stresses to which the guide tubes 24

can be subjected. Such a stress can be a vertical compression stress σ_A , to which the guide tubes 24 are subjected during the contact of the springs 8 of the upper end piece 7 against the upper bearing plate of the core in order to counterbalance the hydrostatic thrust during operation.

Thus, the function f can be, for example, in the form of

$$f(\sigma_{\theta MAX}, \sigma_A) = \sigma_{\theta MAX} + \sigma_A$$

It will be appreciated that this last step, illustrated by the box 58, can be [carried out] performed by separate software which generally [carries out] performs the validation of various design parameters of the assembly 1 based on results provided by various pieces of software each dedicated to taking into consideration specific operating conditions and which include the software which [carries out] performs the steps 42, 44, 46, 48, 50, 52, 54 and 56.

In general terms, the file 43 comprising the data 43 used by the method for the various calculations can comprise the data of Table 1 below.

outside diameter of control rod 10	(m)	Nominal; maximum
inside diameter of upper portion 27	(m)	Nominal; maximum
inside diameter of lower portion 26	(m)	Nominal; maximum
total length of lower portion 26	(m)	
damping travel before impact	(m)	
minimum thickness of wall of lower portion 26	(m)	
maximum roughness of rod 10/tube 24	(m)	Nominal; tolerance
diameter of aperture 29	(m)	
length of aperture 29	(m)	
roughness of aperture 29	(m)	
moving mass M	(kg)	
volumetric mass of liquid	(kg/m ³)	

kinematic viscosity of liquid	(m ² /s)	
c1	(/m)	
c2	(m/s ²)	
Young's modulus of guide tube 24	(Pa)	
Poisson's ratio of guide tube 24		
spring precompression 16	(m)	
preloading of spring 16	(N)	
length of spring 16 with contiguous turns	(m)	
outside diameter of spring 16	(m)	
diameter of wire of spring 16	(m)	
compression when upper head 12 is in contact with upper end piece 7.	(m)	
END		

Table 1

Similarly, the file 49 comprising the results from step 48 can comprise the data of Table 2 below.

5

ΔP_{MAX} : maximum elevated pressure in lower portion 26	(Pa)
Z_{MAX} : corresponding penetration in lower portion 26	(m)
$\sigma_{\theta MAX}$: maximum stress in lower portion 26	(Pa)
F_{max} : maximum force on lower end piece 6	(N)
T_{dur} : duration of fall in lower portion 26 before impact	(s)
V_{fin} : speed of impact of assembly 4 on upper end piece 7	(m/s)

Table 2

The file 57 comprising the results of step 56 can itself contain the data of Table 3 below.

10

F_{MAX} : maximum compression force on spring 16	(N)
h_{MAX} : maximum deflection of spring 16	(m)
τ_{MAX} : approximate maximum stress in spring	(Pa)
	(Pa)
τ_{MAX1} : approximate maximum stress corrected by K_c	
τ_{MAX2} : approximate maximum stress corrected by K (Wahl coefficient)	(Pa)

Table 3

It has been possible to verify by experiment that the maximum elevated pressures and the maximum stresses obtained by means of steps 42, 44, 46 and 48 were reliable. In this manner, the first corresponding part
5 of the method allows reliable guide tubes 24 to be designed. Furthermore, this first part calculates only a single stress which appears to be the pertinent stress for the conditions being considered. Consequently, this first part of the method allows the
10 security margins to be limited during design, and therefore assemblies which are relatively light and economical to be designed.

The second part of the method, which corresponds to
15 steps 50, 52, 54 and 56, also allows maximum stresses to be reliably calculated, as confirmed by experiment.

Thus, the second part of the method allows a reliable design to be arrived at by calculation for the spider
20 springs 16, which design is found to be advantageous in comparison with the method of tests alone which is currently imposed by provisions. It will be appreciated that the second part of the method calculates only the small number of stresses, and in particular those on
25 the axis F2 of the spring 16 nearest the [centre] center axis A of the spring, which are found to be pertinent to the conditions envisaged. In this [manner] manner, the second part of the method allows the design margins to be reduced.

30

In more general terms, the steps 42, 44, 46 and 48, on the one hand, and 50, 52, 54 and 56, on the other, can be carried out by separate pieces of software.

In order to increase the reliability of the calculation, for carrying out the first part of the method it is possible to use, as the passage gap J, the nominal value of the gap, or this nominal value corrected by the manufacturing tolerance, or a value resulting from statistical studies of the distribution of passage gaps J obtained in constructed assemblies.

10 In a variant, it is possible to use a gap value J which is greater for steps 42 and 44 and a smaller gap value J for steps 46 and 48. This allows a high stress value $\sigma_{\theta MAX}$ to be calculated because the speed reached during the fall of the rod 10 in question is high and the volume available in the lower portion 26 for the liquid during damping is small. However, this high stress value is not unrealistic and therefore does not lead to unjustified design margins, as illustrated by the following example.

20 According to a specific variant, the upper value can be a maximum value for gap J which is verified with a given probability, for example, 95%, in constructed assemblies, and the lower value can be a minimum value obtained with the same probability. This variant allows an approximation of the situation where a single pair comprising a guide tube/control rod has minimum gap J, where the maximum stress ($\sigma_{\theta MAX}$) would be reached, and where all the other pairs comprising a guide tube/control rod have the maximum passage gap J, which would be the most extreme case.

In some variants, the first part of the method could also take into consideration forms of the lower

damping portion 26 which are different from those described previously. In this manner, these lower damping portions could have a plurality of successive portions of reduced diameter, optionally separated by
5 portions of increased diameter, generally referred to as cavities. In some variants, the first part of the method is carried out with collared screws 28 which are not perforated by holes 29.

10 In still more general terms, the first part and the second part of the design method described can be used independently of each other. In this manner, it is possible to carry out the second part relating to the design of the spring 16 without referring to the
15 calculation of the elevated pressure ΔP and the stress σ_{0MAX} .

ABSTRACT

A method to design a nuclear fuel assembly having the following steps including establishing the falling speed of the control rod upon entry into the lower damping portion when the control cluster falls in the event of a shutdown of the nuclear reactor, establishing, based on the falling speed established in step a), the progression of the falling speed of the control rod in the lower damping portion, establishing, based on the progression of the speed established in step b), a maximum elevated pressure produced in the liquid contained in the lower damping portion, and establishing, based on the maximum elevated pressure established in step c), a maximum circumferential stress produced in the lower damping portion.